



NutriDoser Range

Economic | Versatile | Efficient

Locally developed dosing unit range




After identifying various needs in the market, our local team put their heads together to develop this range fit for Southern African farms. The NutriDoser fertigation unit range. It offers a competitive, user-friendly, and compact fertigation solution to the market. This customer-driven innovation will make fertigation technology more accessible to a wider range of farmers. It is a simple and economic range developed with the farmer in mind.

Benefits & Features

ERGONOMIC	The unit's aluminum frame is designed with the same dimensions for all unit types. This creates versatility and efficiency as it allows units to be combined and adapted as necessary.
MODULAR	Different NutriDoser units can be combined into a single system with a common inlet manifold and separate outlet manifolds.
PROBLEM-SOLVING	The common inlet and separate outlet manifolds prevent gypsum build-up when possibly incompatible fertilizers are used. Build-up may lead to clogging of pipes and pump failures.
FLEXIBLE	Channels with differing capacities can be combined on one unit. This lowers costs as you can use a channel with the appropriate capacity for each task.
ECONOMICAL	NutriDoser's flexibility, modularity and versatility, combined with the fact that it is manufactured locally, makes it a very economical solution.
RELIABLE	Only quality parts from known industry suppliers are used.
COMPACT	Units have a small frame making it easier to accommodate and ship. If necessary, it can be shipped pre-assembled or semi-assembled and easily assembled on site. Different units are built with similar parts, reducing replacement part stockholding.
VERSATILE	Easily slots into existing systems. Compatible with most controllers – not only Netafim controllers. Can be added to existing dosing unit systems to add capacity to the system.
LOW-MAINTENANCE	Parts are easy to replace without detailed technical knowledge. Units with Venturis have virtually no moving parts, limiting risk of breakdown and required maintenance.

Unit Variations

Total of 18 different unit variations (product codes) available. Consist of the main models as shown below. Speak to your irrigation supplier or Netafim Technical Advisor about the full range's unit specifications and application.




NutriDoser V (3 Channel)

- 2 or 3 x 150 l/h or 400 l/h channels
- Standard pressure or high pressure
- Controller, meters & EC/pH control are optional

NutriDoser V (1 channel)

- 1 x 400 l/h or 1000 l/h channel
- Single-channel unit to answer in specific needs
- Standard pressure or high pressure
- Controller Optional



NutriDoser V ADD-ON (3 Channel)

- Adds on to an existing NutriDoser V making it a 3 + 3 split unit
- Separate machines with one inlet but separate outlets to mainline

NutriDoser MAN

- 1 x Chemical 1000 l/h channels
- 2 x Fertiliser 4000 l/h channels
- One channel active at a time
- Standard pressure or high pressure
- Controller optional

Unit Name Legend

Example unit names:

NutriDoser-V 3x400 S12 CM5-7 SP

NutriDoser-V 3x400 S12 CM5-7 SP ADD-ON

NutriDoser-V 1x400 S12 CM1-8 SP VFM

NutriDoser-V 1x150 S12 CM1-8 SP VFM

LEGEND	DESCRIPTION	LEGEND	DESCRIPTION
V	Venturi	3x400	Number of channels x Channel capacity (ℓ/h)
P	Pump	CM5-7	Pump size and type
MAN	Manual Valve	QN5	Fertiliser meter type/presence
S12	S12 Solenoid	D	Flow rate display
S22	S22 Solenoid	VFM	Visual flow meter
SP	Standard Pressure	ADD-ON	Add on to an existing unit
HP	High Pressure	Q	Flow

NutriDoser Add-ons

- Add-on Injection Units
- Add-on EC/pH Set
- Add-on EC/pH Manifold for NutriDoser
- Add-on Mixing Chamber
- Add-on SF Fertilizer meter
- Add-on QN 2.5 Fertilizer meter
- Add-on Pro Controller
- Add-on Junior Controller
- Add-on PSV for 1 Channel unit outlet



Selection Information for EC/pH control

DOSING UNIT TYPE	FOR EC CONTROL	MIXING CHAMBER PRESENT	% FLOW VARIANCE FROM SMALLEST TO LARGEST BLOCK	TOTAL ALKALINITY IN	IRRIGATION PULSE	CONTROL CYCLE
NutriDoser V (3 Channel)	Yes	No	25	≤ 3 mEq/ℓ	≥ 8 minutes	6 to 15 seconds
	Yes	Yes	10	≤ 2 mEq/ℓ	≥ 4 minutes	6 to 15 seconds
	No	No		No Limit		

Netafim Southern & East Africa

Industrial Road, Kraaifontein, Cape Town, 7570

T : +27 21 987 0477 | WhatsApp: +27 60 983 6058

www.netafim.co.za | infoza@netafim.com



Dosing Unit		Dosing Channels					Irrigation System		
Model	/In Outlet	Qty		Operation	Max & min calibration (% time open)		Pressure at inlet		Q Min
					100	Min			
	(mm) PVC	On Unit	Parallel operation	Suction Mechanism	Flow rate (ℓ/h) per channel for max & min calibration		Min (m)	Max (m)	(m³/h)
NutriDoser-V 3x400 S12 CM5-7 SP	40	3	3	Venturi	400	50	25	50	8
NutriDoser-V 3x400 S12 CM5-10 HP	40	3	3	Venturi	400	50	30	80	8
NutriDoser-V 3x150 S12 CM5-7 SP	40	3	3	Venturi	150	50	25	50	8
NutriDoser-V 3x150 S12 CM5-10 HP	40	3	3	Venturi	150	50	30	80	8
NutriDoser-V 3x400 S12 CM5-7 SP ADD-ON	40	3	3	Venturi	400	50	25	50	16
NutriDoser-V 3x400 S12 CM5-10 HP ADD-ON	40	3	3	Venturi	400	50	30	80	16
NutriDoser-V 3x150 S12 CM5-7 SP ADD-ON	40	3	3	Venturi	150	50	25	50	16
NutriDoser-V 3x150 S12 CM5-10 HP ADD-ON	40	3	3	Venturi	150	50	30	80	16
NutriDoser-V 1x400 S12 CM1-8 SP VFM	40	1	1	Venturi	400	50	25	50	3
NutriDoser-V 1x400 S12 CM1-12 HP VFM	40	1	1	Venturi	400	50	30	80	3
NutriDoser-V 1x150 S12 CM1-8 SP VFM	40	1	1	Venturi	150	50	25	50	3
NutriDoser-V 1x150 S12 CM1-12 HP VFM	40	1	1	Venturi	150	50	30	80	3
NutriDoser-V 1x400 S12 CM1-8 SP VFM D	40	1	1	Venturi	400	50	25	50	3
NutriDoser-V 1x400 S12 CM1-12 HP VFM D	40	1	1	Venturi	400	50	30	80	3
NutriDoser-V 1x1000 S22 CM5-7 QN2.5 D SP	40	1	1	Venturi	1000	100	25	50	8
NutriDoser-V 1x1000 S22 CM5-10 QN2.5 D HP	40	1	1	Venturi	1000	100	25	80	8
NutriDoser - MAN 1VQ1 + 3PQ4 CM5-7 SP QN5.0	40	1+3	1	Venturi/ Pump	1000/ 4000	100/ 1000	25	50	*
NutriDoser - MAN 1VQ1 + 3PQ4 CM5-10 HP QN5.0	40	1+3	1	Venturi/ Pump	1000/ 4000	100/ 1000	30	80	*

* Not applicable